

WARRANTY
For
AVERY DENNISON® T-1500/T-1600 Reflective Sheeting
To ASTM Type I Reflectivity Specifications

Avery Dennison Corporation ("Avery Dennison") warrants that its Avery Dennison® T-1500/T-1600 Engineer Grade reflective sheeting will retain its effectiveness as a component of traffic control and guidance signs, and will meet the following minimum retroreflective values for the period specified:

Minimum Coefficient of Retroreflection (cd/lx/m²)*
(@ 0.2° observation angle, -4.0° entrance angle)

Color	Initial Coefficient	7 years from date of sign fabrication
White	70	35
Yellow	50	25
Orange	25	12.5**
Green	9	4.5
Red	14	7
Blue	4	2
Brown	1	.5

*For transparent color screenprinted areas using Avery Dennison supplied or approved inks on Avery Dennison® T-1500/T-1600 white sheeting, values shall be a minimum of 70% of the above. All measurements will be made after cleaning in accordance with Avery Dennison's recommended procedure.
**3 Years

If within 7 years of sign fabrication, the sheeting deteriorates due to natural causes to the extent that the sign fails to retain the minimum reflectivity values warranted for the 7-year period, Avery Dennison will furnish a replacement amount of like sheeting at no cost to enable the sign surface to be restored to its warranted effectiveness.

WARRANTY CONDITIONS. This warranty shall be effective only if all of the following conditions are met:

The failure must have resulted solely from a manufacturing defect or deterioration of the sheeting due to natural causes. Without limiting the generality of the foregoing, there is no warranty for the failure of the sheeting due to improper sign fabrication, improper storage, handling, installation, or maintenance, or failure of the sign substrate, or vandalism or malicious mischief. Slight color fading, cracking, chalking, edge lifting, or slight reduction in gloss or reflectivity will not materially detract from appearance and does not constitute a breach of warranty.

Avery Dennison has published instructional bulletins pertaining to the storage, handling, and cleaning of sheeting, approved sheeting substrates, and sheeting application procedures (collectively, the "Procedures"). The sheeting must have been processed and applied to blank sign material in accordance with the Procedures, as such may be amended from time to time. The sign dating, warranty registration, and claim procedures promulgated by Avery Dennison must be followed, and failure to follow such procedures shall void this warranty. Replacement sheeting carries only the unexpired warranty of the sheeting it replaces.

WARRANTY LIMITATIONS. The remedies provided under this warranty are exclusive. Avery Dennison shall not be liable for any direct, indirect, incidental or consequential damages or specific relief, and, except as specifically provided herein, in no event shall Avery Dennison's liability hereunder exceed the remedies specifically set forth in this warranty. **THIS WARRANTY IS GIVEN IN LIEU OF ALL OTHERS. ANY AND ALL OTHER WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING IMPLIED WARRANTIES OF MERCHANT-ABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE HEREBY DISCLAIMED.**



Avery Dennison Corporation, Reflective Films Division
6565 West Howard Street, Niles, Illinois 60714 USA